

Technical Data



MULTISOLVE is a safe and fast multipurpose solvent degreaser that leaves no oily film
 MULTISOLVE is a 100% aliphatic hydrocarbon solvent that contains no recycled solvents
 MULTISOLVE is safe to use on most plastics as well as on painted surfaces, vinyl and glass
 When using MULTISOLVE, adequate ventilation is recommended.

State at 20°C :	liquid
Colour :	colourless
Boiling point/range :	140° C – 171° C
Specific gravity :	0,740 – 0,750 @ 25° C
Vapour Pressure :	1,0 Kpa @ 20° C
Flash Point :	+28°C
Spontaneous ignition :	+210°C

APPLICATIONS

Degreasing and cleaning mechanical parts, motor, brakes, suspension.
 Cleaning tools and workshop equipment – attacks no plastics.
 Removal of stickers or masking tape adhesive residues.
 Removal of previous grease layers before re-lubricating, e.g. door hinges. Multisolve does not corrode the paint.
 Removal of trims and bumper strips without damaging.
 Multisolve dissolves the adhesive layer of double sided adhesive tape.
 Removal of tar and other coating stains.
 Finishing of joints sealed with CT1.
 Cleaning of paint and undercoat before spray-painting (Multisolve removes wax and silicone, always use a 2-cloth system).
 Degreasing and cleaning of all surfaces before using C-Tec adhesives and sealants.