



SAFETY DATA SHEET

Kilrock Wood & Laminate Floor Cleaner Spray

Compilation date: 24/07/2023

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Kilrock Wood & Laminate Floor Cleaner Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against Identified uses

Cleaning agent.

Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Manufacturer : Kilrock Products Ltd Units
 1b/2b Alma Road Industrial Estate
 Chesham
 Buckinghamshire
 HP5 3HB United Kingdom
 T +44 (0)1494 793900
 info@kilrock.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1494 793900 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318
Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H315 Causes skin irritation.
 H318 Causes serious eye damage.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear protective gloves, eye and face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/ doctor.
 P501 Dispose of contents/ container in accordance with national regulations.

Kilrock Wood & Laminate Floor Cleaner Spray

Contains DISODIUM METASILICATE

Detergent labelling < 5% aliphatic hydrocarbons, < 5% EDTA and salts thereof

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DISODIUM METASILICATE 1-5%		
CAS number: 6834-92-0	EC number: 229-912-9	REACH registration number: 01-2119449811-37-XXXX
Classification Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335		
(2-methoxymethylethoxy) propanol 1-5%		
CAS number: 34590-94-8	EC number: 252-104-2	REACH registration number: 01-2119450011-60-XXXX
Classification Not Classified		
SODIUM CARBONATE 1-5%		
CAS number: 497-19-8	EC number: 207-838-8	REACH registration number: 01-2119485498-19-XXXX
Classification Eye Irrit. 2 - H319		
Tetrasodium ethylene diamine tetraacetate 1-5%		
CAS number: 64-02-8	EC number: 200-573-9	REACH registration number: 01-2119486762-27-XXXX
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H332 Eye Dam. 1 - H318 STOT RE 2 - H373		

Kilrock Wood & Laminate Floor Cleaner Spray

Sulphuric acid, mono-C12-14-alkyl esters, sodium salts <1% CAS number: 85586-07-8 EC number: 287-809-4 REACH registration number: 01-2119489463-28-XXXX
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412
D-Glucopyranose, oligomers, decyl octyl glycosides <1% CAS number: 68515-73-1 EC number: 500-220-1 REACH registration number: 01-2119488530-36-XXXX
Classification Eye Dam. 1 - H318
Alcohols, C12-C14 (even numbered), ethoxylated<2.5EO, sulphates, sodium salts <1% CAS number: 68891-38-3 EC number: 500-234-8 REACH registration number: 01-2119488639-16-XXXX
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Show this Safety Data Sheet to the medical personnel. Get medical attention immediately. If medical advice is needed, have product container or label at hand.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Rinse with water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Coughing, chest tightness, feeling of chest pressure.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Kilrock Wood & Laminate Floor Cleaner Spray

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Ammonia or amines. Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not touch or walk into spilled material. Avoid contact with skin, eyes and clothing. Take care as floors and other surfaces may become slippery. Avoid contact with contaminated tools and objects. Do not handle broken packages without protective equipment. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective gloves, eye and face protection. Avoid contact with skin, eyes and clothing. Avoid contact with contaminated tools and objects. Avoid release to the environment. Do not reuse empty containers. Do not use in paint spraying equipment. Do not empty into drains. Do not eat, drink or smoke when using this product. Do not handle broken packages without protective equipment. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 4°C and 40°C.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Kilrock Wood & Laminate Floor Cleaner Spray

Occupational exposure limits

(2-methoxymethylethoxy) propanol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

DISODIUM METASILICATE (CAS: 6834-92-0)

DNEL	Industry - Dermal; Long term : 1.49 mg/kg/day Industry - Inhalation; Long term : 6.22 mg/m ³ Consumer - Dermal; Long term : 0.74 mg/kg/day Consumer - Inhalation; Long term : 1.55 mg/m ³ Consumer - Oral; Long term : 0.74
PNEC	Fresh water; 7.5 mg/l marine water; 1 mg/l Intermittent release; 7.5 mg/l STP; 1000 mg/l

(2-methoxymethylethoxy) propanol (CAS: 34590-94-8)

DNEL	Industry - Dermal; Long term : 65 mg/kg/day Industry - Inhalation; Long term : 310 mg/m ³ Consumer - Inhalation; Long term : 37.2 mg/m ³ Consumer - Dermal; Long term : 15 mg/kg/day Consumer - Oral; Long term : 1.67 mg/kg/day
PNEC	- Fresh water; 19 mg/l - marine water; 1.9 mg/l - Intermittent release; 19 mg/l - STP; 4168 mg/l - Sediment (Freshwater); 70.2 mg/kg - Sediment (Marinewater); 7.02 mg/kg - Soil; 2.74 mg/kg

SODIUM CARBONATE (CAS: 497-19-8)

DNEL	Industry - Inhalation; Long term local effects: 10 mg/m ³ Consumer - Inhalation; Short term local effects: 10 mg/m ³
-------------	---

Tetrasodium ethylene diamine tetraacetate (CAS: 64-02-8)

DNEL	Workers - Inhalation; Long term systemic effects, local effects: 1.5 mg/m ³ Workers - Inhalation; Short term systemic effects, local effects: 3 mg/m ³ Consumer - Inhalation; Long term local effects, systemic effects: 0.6 mg/m ³ Consumer - Inhalation; Short term systemic effects, local effects: 1.2 mg/m ³ Consumer - Oral; Long term local effects, systemic effects: 25 mg/m ³
PNEC	- Fresh water; 2.2 mg/l - marine water; 0.22 mg/l - Intermittent release; 1.2 mg/l - STP; 43 mg/l - Soil; 0.72 mg/kg

Sulphuric acid, mono-C12-14-alkyl esters, sodium salts (CAS: 85586-07-8)

Kilrock Wood & Laminate Floor Cleaner Spray

DNEL	Workers - Dermal; Long term systemic effects: 4060 mg/kg/day Workers - Inhalation; Long term systemic effects: 285 mg/m ³ General population - Oral; Long term systemic effects: 24 mg/kg/day General population - Dermal; Long term systemic effects: 2440 mg/kg/day General population - Inhalation; Long term systemic effects: 85 mg/m ³
PNEC	- Fresh water; 0.102 mg/l - marine water; 0.01 mg/l - Intermittent release; 0.036 mg/l - Sediment (Freshwater); 3.58 mg/kg - Sediment (Marinewater); 0.358 mg/kg - Soil; 0.654 mg/kg - STP; 1084 mg/l

D-Glucopyranose, oligomers, decyl octyl glycosides (CAS: 68515-73-1)

DNEL	Workers - Dermal; Long term systemic effects: 595000 mg/kg/day Workers - Inhalation; Long term systemic effects: 420 mg/m ³ Consumer - Dermal; Long term systemic effects: 357000 mg/kg/day Consumer - Inhalation; Long term systemic effects: 124 mg/m ³ Consumer - Oral; Long term systemic effects: 35.7 mg/kg/day
PNEC	- Fresh water; 0.1 mg/l - marine water; 0.01 mg/l - STP; 560 mg/l - Soil; 0.654 mg/kg - Sediment (Freshwater); 0.487 mg/kg - Sediment (Marinewater); 0.048 mg/kg

Alcohols, C12-C14 (even numbered), ethoxylated<2.5EO, sulphates, sodium salts (CAS: 68891-38-3)

DNEL	Industry - Dermal; Long term systemic effects: 2750 mg/kg/day Industry - Inhalation; Long term systemic effects: 175 mg/m ³ Consumer - Oral; Long term systemic effects: 15 mg/kg/day Consumer - Dermal; Long term systemic effects: 1650 mg/kg/day Consumer - Inhalation; Long term systemic effects: 52 mg/m ³
PNEC	- Fresh water; 0.24 mg/l - marine water; 0.024 mg/l - Intermittent release; 0.071 mg/l - Sediment (Freshwater); 5.45 mg/kg - Sediment (Marinewater); 0.545 mg/kg - Soil; 0.946 mg/kg - STP; 10000 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients.

Kilrock Wood & Laminate Floor Cleaner Spray

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Protective gloves should have a minimum thickness of 0.15 mm. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Rubber (natural, latex). Neoprene.
Other skin and body protection	Provide eyewash station.
Hygiene measures	Wash hands thoroughly after handling. Wash contaminated clothing before reuse.
Respiratory protection	No specific requirements are anticipated under normal conditions of use. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Particulate filters should comply with European Standard EN143. Disposable filtering half mask respirators should comply with European Standard EN149 or EN405. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Organic vapour + dust and mist filter.
Environmental exposure controls	Store in a demarcated bunded area to prevent release to drains and/or watercourses. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Mild.
Odour threshold	Not determined.
pH	pH (concentrated solution): >11.5
Melting point	Not determined.

Kilrock Wood & Laminate Floor Cleaner Spray

Initial boiling point and range	Not determined.
Flash point	Not determined.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not determined.
Relative density	~ 1.02 @ 25°C
Solubility(ies)	Soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	There are no chemical groups present in the product that are associated with explosive properties.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidising properties.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Other information Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Kilrock Wood & Laminate Floor Cleaner Spray

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Ammonia or amines. Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 177,832.84

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (gases ppm) 1,123,943.49

ATE inhalation (vapours mg/l) 2,747.42

ATE inhalation (dusts/mists mg/l) 374.65

Skin corrosion/irritation

Extreme pH ≥ 11.5

Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed. No testing is needed. Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Inhalation

Coughing, chest tightness, feeling of chest pressure.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Causes skin irritation.

Kilrock Wood & Laminate Floor Cleaner Spray

Eye contact	Causes serious eye damage.
Acute and chronic health hazards	A single exposure may cause the following adverse effects: Corneal damage. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: Product has a defatting effect on skin.
Route of exposure	Dermal Skin and/or eye contact
Target organs	Eyes Skin
Medical symptoms	Dry skin. Skin irritation.

Toxicological information on ingredients.

DISODIUM METASILICATE

Acute toxicity - oral

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE dermal (mg/kg) 5,001.0

(2-methoxymethylethoxy) propanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,382.66

Species Rat

ATE oral (mg/kg) 5,382.66

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,001.0

Species Rabbit

ATE dermal (mg/kg) 5,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 3,080.0

Species Rat

ATE inhalation (vapours mg/l) 3,080.0

SODIUM CARBONATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,800.0

Species Rat

Kilrock Wood & Laminate Floor Cleaner Spray

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.01
mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,000.01

Tetrasodium ethylene diamine tetraacetate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 1,780.0
mg/kg)

Species Rat

ATE oral (mg/kg) 1,780.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

ATE inhalation (gases 11,250.0
ppm)

ATE inhalation (vapours 27.5
mg/l)

ATE inhalation 3.75
(dusts/mists mg/l)

Sulphuric acid, mono-C12-14-alkyl esters, sodium salts

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 1,800.0
mg/kg)

Species Rat

ATE oral (mg/kg) 1,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0
mg/kg)

Species Rat

D-Glucopyranose, oligomers, decyl octyl glycosides

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,001.0
mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0
mg/kg)

Species Rabbit

Kilrock Wood & Laminate Floor Cleaner Spray

ATE dermal (mg/kg) 2,001.0

Alcohols, C12-C14 (even numbered), ethoxylated<2.5EO, sulphates, sodium salts

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 4,100.0

Species Rat

Notes (oral LD₅₀)

ATE oral (mg/kg) 4,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rat

ATE dermal (mg/kg) 2,001.0

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Ecological information on ingredients.

DISODIUM METASILICATE

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 210 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1700 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 207 mg/l, Scenedesmus subspicatus

(2-methoxymethylethoxy) propanol

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: > 1000 mg/l, Poecilia reticulata (Guppy)

Acute toxicity - aquatic invertebrates NOEC, >: > 0.5 mg/l, Daphnia magna
EC₅₀, 48 hours: 1919 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: > 969 mg/l, Selenastrum capricornutum

SODIUM CARBONATE

Kilrock Wood & Laminate Floor Cleaner Spray

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 300 mg/l, *Lepomis macrochirus* (Bluegill)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 265 mg/l, *Daphnia magna*

Tetrasodium ethylene diamine tetraacetate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 100 mg/l, *Lepomis macrochirus* (Bluegill)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, *Daphnia magna*

Sulphuric acid, mono-C12-14-alkyl esters, sodium salts

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 3.6 mg/l, *Oncorhynchus mykiss* (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 4.7 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants EC₅₀, 72 hours: >20 mg/l, *Scenedesmus subspicatus*

Acute toxicity - microorganisms EC₀, 16 hours: 409 mg/l, Activated sludge

D-Glucopyranose, oligomers, decyl octyl glycosides

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, *Brachydanio rerio* (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, *Daphnia magna*

Alcohols, C12-C14 (even numbered), ethoxylated<2.5EO, sulphates, sodium salts

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 7.1 mg/l, *Brachydanio rerio* (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 7.4 mg/l, *Daphnia magna*
NOEC, 48 hours: 0.27 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants EC₅₀, 72 hours: 27 mg/l, *Scenedesmus subspicatus*

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Kilrock Wood & Laminate Floor Cleaner Spray

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

Special Provisions note

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

Kilrock Wood & Laminate Floor Cleaner Spray

EU legislation

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents (as amended).
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
 Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 NOEC: No Observed Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 PNEC: Predicted No Effect Concentration.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 UN: United Nations.
 vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Met. Corr. = Corrosive to metals
 Skin Corr. = Skin corrosion
 Eye Dam. = Serious eye damage
 STOT SE = Specific target organ toxicity-single exposure
 Skin Irrit. = Skin irritation
 Acute Tox. = Acute toxicity
 STOT RE = Specific target organ toxicity-repeated exposure
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Classification procedures according to Regulation (EC) 1272/2008

Skin Irrit. 2 - H315, Eye Dam. 1 - H318: Calculation method.

Revision date 27/04/2021

Revision 1.0

SDS number 30956

Kilrock Wood & Laminate Floor Cleaner Spray

Hazard statements in full

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs (Respiratory system, lungs) through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.